

AES DRILLING FLUIDS

BENEFITS

- Provides superior low-shear suspension for optimal hole cleaning and minimized risk of sag
- Enhances hole cleaning without significantly increasing viscosity
- Performs across a broad range of temperatures

APPLICATIONS

- Typically added at 1 - 5 lb/bbl for most applications
- Performs in conjunction with ENERVIS RM[†]
- Pilot testing will aid to determine the appropriate concentration for a specific scenario

PHYSICAL PROPERTIES

- Appearance: Light tan powder
- Specific Gravity: 1.65 - 1.7

AES VIS LS[†]

AES VIS LS is an organophilic clay that provides increased low shear rheology with minimal overall increase in viscosity and gel strengths



AES VIS LS organophilic clay


Treatment Recommendations

Typical concentrations range from 1 to 5 lb/bbl for most applications. For system treatments, add AES VIS LS in 0.5 to 1 lb/bbl increments and observe property changes. Add AES VIS LS through the hopper and allow product to shear.

Pilot testing recommended to determine the appropriate concentration for a specific scenario.

Packaging and Handling

AES VIS LS is available in 50 lb sacks. Handle AES VIS LS as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS

www.aesfluids.com

info@aesfluids.com

888-556-4533

Revision 1.00

© 2018 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. *Marks of AES Drilling Fluids, LLC.

