

AES DRILLING FLUIDS

BENEFITS

- Engineered to minimize fluid loss
- Aids in increasing low shear viscosity and contributes to overall suspension properties of the fluid
- Effective in high temperature environments (> 400°F)

APPLICATIONS

- Typically added at 2 - 4 lb/bbl for most applications
- Performs in conjunction with ENERSPERSE[†]
- Supplemental Treatment recommended prior to logging and casing runs

PHYSICAL PROPERTIES

- Appearance: White powder
- Specific Gravity: 1.13

DURATEC ER[†]

DURATEC ER is a high performance polymeric fluid loss control agent designed for the EnerREACH[†] system



Filtercake (right) and filtrate (left) of oil based fluid system using DURATEC ER at 300° F. As part of a properly designed system, DURATEC ER provides excellent filtration control.


Treatment Recommendations

Typical concentrations range from 2 to 4 lb/bbl for most applications; however, higher concentrations may be required depending on the desired fluid loss control. DURATEC ER performs in conjunction with ENERSPERSE. Prior to logging or casing runs, supplemental treatment with DURATEC ER will aid to condition the wellbore.

Pilot testing recommended to determine the appropriate concentration for a specific scenario.

Packaging and Handling

DURATEC ER is available in 30 lb sacks. Handle DURATEC ER as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS

www.aesfluids.com

info@aesfluids.com

888-556-4533

Revision 1.00

© 2018 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. *Marks of AES Drilling Fluids, LLC.

