

#### **BENEFITS**

- Effectively reduces yield point and gel strengths
- Reduces surge pressures and friction pressure losses

#### **APPLICATIONS**

- ENERSPERSE is a component for the EnerREACH system
- Typically additions of 0.25 lb/bbl are effective to treat the active system
- Supplemental treatment recommended prior to logging and casing runs

# PHYSICAL PROPERTIES

- Appearance: Light tan powder
- Specific Gravity: 0.87
- Flash Point: >240°F

# **ENERSPERSE**<sup>†</sup>

ENERSPERSE is a concentrated dispersant/thinner designed to reduce viscosity in the EnerREACH† system



**ENERSPERSE** dispersant/thinner

### **Treatment Recommendations**

Typical additions of 0.25 lb/bbl as part of treating the active system; although, higher concentrations may be required for more extreme conditions. ENERSPERSE can be used as a supplemental treatment prior to logging and casing runs.

Pilot testing recommended to determine the appropriate concentration for a specific scenario.

## **Packaging and Handling**

ENERSPERSE is available in 5 gal pails and 55 gal drums. Handle ENERSPERSE as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



www.aesfluids.com

info@aesfluids.com

888-556-4533

Revision 1.00

© 2018 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. \*Marks of AES Drilling Fluids, LLC.

