

AES DRILLING FLUIDS

BENEFITS

- Rapid sealing and bridging of permeable or fractured zones
- Designed to minimize risk of plugging downhole equipment
- Does not alter fluid properties (inert solid)

APPLICATIONS

- Typically added at 10 - 30 lb/bbl for sweeps or 3 - 7 lb/bbl for seepage loss control
- Performs as standalone product or in combination with other materials
- Higher concentrations may be required for extreme conditions

PHYSICAL PROPERTIES

- Particle size distribution (Typical Percent retained, microns)

D ₁₀	14
D ₅₀	90
D ₉₀	300

- Appearance: Granular fibrous blend
- Specific Gravity: 1.4

MULTIFIBER F[†]

MULTIFIBER F is a proprietary blend of fine fibrous material used to prevent or treat lost circulation and bridge permeable formations




MULTIFIBER F lost circulation additive

Treatment Recommendations

Treatments typically range from 10 to 30 lb/bbl for sweeps. As part of the active system, concentrations range from 3 to 7 lb/bbl. While MULTIFIBER F is designed to minimize risk of plugging downhole tools, verify compatibility with supplier representatives before use.

Packaging and Handling

MULTIFIBER F is available in 25 lb sacks. Handle MULTIFIBER F as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS

www.aesfluids.com

info@aesfluids.com

888-556-4533

Revision 1.00

© 2018 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. *Marks of AES Drilling Fluids, LLC.

