

BLUE MAX[†]



BENEFITS

- Minimizes bottomhole assembly and bit balling
- Useful for rig clean-up - non-caustic and biodegradable
- Performs in most water based systems



APPLICATIONS

- 0.5 - 5% by volume (typical) or 1 pail per sweep
- As needed for rig cleaning applications
- Can be added directly to the hopper



PHYSICAL PROPERTIES

- Appearance: Blue liquid
- Specific Gravity: 1.02 - 1.03

BLUE MAX is a concentrated, multi-purpose drilling surfactant that aids to prevent bit balling. It also performs as a cleaning surfactant for rig equipment.



BLUE MAX Surfactant

TREATMENT RECOMMENDATIONS

Typical concentrations range between 0.5 to 5.0% by volume in the active system or 1 pail per sweep. BLUE MAX can be added directly to hopper and is compatible with most water based systems. Use as needed for rig cleaning applications.

PACKAGING AND HANDLING

BLUE MAX is available in 5 gallon pails. Handle BLUE MAX as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS

www.aesfluids.com

☎ Phone : 281 556 5628

✉ Email : info@aesfluids.com

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

