

ENERPLUS[†]



BENEFITS

Provides cuttings encapsulation and shale stabilization

Aids solids removal by flocculation

Enhances filter cake quality



APPLICATIONS

Typically added at 0.75 - 3.0 lb/bbl for most applications

Performs across a broad range of water-based systems

Higher concentrations may be needed in NaCl and KCl based fluids



PHYSICAL PROPERTIES

- Appearance: Cream colored liquid
- Specific Gravity: 1.03 - 1.06
- Freeze Point: 5°F
- Flash Point: > 200°F

ENERPLUS is a high molecular weight PHPA that provides cuttings encapsulation and shale stabilization.



ENERPLUS liquid anionic polymer

TREATMENT RECOMMENDATIONS

Typical concentrations range between 0.75 to 3.0 lb/bbl for most applications; however, higher concentrations may be required in NaCl and KCl based fluid systems. ENERPLUS sweeps are effective for periodic hole cleaning and can be used across a broad range of water-based systems. If frozen, ENERPLUS needs to be fully thawed and agitated prior to use.

PACKAGING AND HANDLING

ENERPLUS is available in 5 gallon pails. Handle ENERPLUS as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS

www.aesfluids.com

☎ Phone : 281 556 5628

✉ Email : info@aesfluids.com

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

