

ESM HDD[†]



BENEFITS

Maintains and enhances unique shear thinning properties to the EnerSEAL HDD[†] system

Stabilizes system from contaminants and minimizes dilution requirements

NSF Certified



APPLICATIONS

EnerSEAL HDD drilling fluid system for horizontal directional drilling/trenchless applications

Typical concentrations for preparation and maintenance range between 2.3 and 7.1 pounds per 100 gallons



PHYSICAL PROPERTIES

- Appearance: White/off-white or gray powder
- Bulk Density: 40 - 48 lb/ft³
- Dispersion: Forms a cloudy dispersion in water

ESM HDD is a proprietary mix of metal oxides, conditioners, and control agents used to prepare and maintain the EnerSEAL HDD system. ESM HDD provides EnerSEAL HDD rheological properties and enhances system tolerance to contaminants.



TREATMENT RECOMMENDATIONS

ESM HDD is a dry powder used to prepare and maintain the EnerSEAL HDD system. Concentrations to prepare and maintain EnerSEAL HDD range from 2.3 to 7.1 pounds of product per 100 gallons. Pilot test anionic products or thinners with EnerSEAL HDD prior to addition.

ESM HDD is mildly hygroscopic, meaning a slight reduction in activity will occur over time in high humidity environments.

PACKAGING AND HANDLING

ESM HDD is available in 50 lb multi-walled sacks. Handle ESM HDD as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



Certified to
NSF/ANSI 60



AES DRILLING FLUIDS

www.aesfluids.com

☎ Phone : 281 556 5628

✉ Email : info@aesfluids.com

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

