

FLR[†]



BENEFITS

Enhances filter cake quality and thickness, lowering overall fluid loss

Does not adversely affect rheology



APPLICATIONS

2 to 10 lb/bbl (typical) for most fluid loss applications

Supplemental treatment recommended prior to logging and casing runs



PHYSICAL PROPERTIES

- Appearance: Black powder
- Specific Gravity: 1.28

FLR is a blended fluid loss control agent for invert emulsion drilling fluid systems.



FLR fluid loss control additive

TREATMENT RECOMMENDATIONS

Typical concentrations range from 2 to 10 lb/bbl for most fluid loss applications; although under extreme conditions higher concentrations may be required. Supplemental treatment with FLR is recommended prior to logging and casing runs.

If large quantities of product are required to achieve target properties, consider using FLR PLUS.

Pilot testing can determine the appropriate concentration. FLR has a minimal impact on rheology and performs across a wide range of drilling fluid densities and temperatures.

PACKAGING AND HANDLING

FLR is available in 50 lb sacks. Handle FLR as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS

www.aesfluids.com

☎ Phone : 281 556 5628

✉ Email : info@aesfluids.com

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

