

# POLYPRO G<sup>†</sup>



## BENEFITS

Stabilizes reactive clay formations

Aids in torque reduction and minimizes bit balling

Improves fluid lubricity



## APPLICATIONS

2.0 - 5.0% v/v (typical) for most applications

Higher concentrations may be required for extreme conditions

Periodic treatments are necessary to maintain desired concentrations



## PHYSICAL PROPERTIES

- Appearance: Yellow amber liquid
- Specific Gravity: 1.03 - 1.13
- Flash Point: > 400°F

POLYPRO G is a proprietary blend of glycols that improves lubricity and provides shale inhibition in water based systems.



POLYPRO G lubricity and shale inhibition additive

## TREATMENT RECOMMENDATIONS

Typical concentrations range between 2 to 5% by volume for most applications, although under extreme conditions higher concentrations may be required. Supplemental treatments are required to maintain a desired concentration.

## PACKAGING AND HANDLING

POLYPRO G is available in bulk. Handle POLYPRO G as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



# **AES DRILLING FLUIDS**

[www.aesfluids.com](http://www.aesfluids.com)

☎ Phone : 281 556 5628

✉ Email : [info@aesfluids.com](mailto:info@aesfluids.com)

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

