

SILVERSEAL[†]



BENEFITS

Enhances filter cake quality, lowering overall fluid loss

Reduces torque and drag

Designed for water-based and invert emulsion systems



APPLICATIONS

10 - 30 lb/bbl for sweeps or 5 - 9 lb/bbl maintained in the active system (typical)

Performs in conjunction with fibers, asphalts, and calcium carbonate

Supplemental treatment recommended prior to logging and casing runs



PHYSICAL PROPERTIES

- Appearance: Gray powder
- Specific Gravity: 2.1

SILVERSEAL is a proprietary blend of sized bridging and sealing components developed to minimize fluid loss in permeable formations.



SILVERSEAL particle blend

TREATMENT RECOMMENDATIONS

When used in sweeps, typical concentrations range from 10 to 30 lb/bbl. As part of the active system, concentrations range between 5 and 9 lb/bbl. Supplemental treatment prior to logging or casing runs enhances filter cake quality to lower torque and reduce differential sticking risk.

As with any lost circulation material, confirm that surface and downhole equipment will tolerate the distribution and concentration of particles present prior to use.

Particle Size Distribution
(typical, microns)

D ₁₀	3
D ₅₀	18
D ₉₀	110

PACKAGING AND HANDLING

SILVERSEAL is available in 50 lb sacks. Handle SILVERSEAL as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS

www.aesfluids.com

☎ Phone : 281 556 5628

✉ Email : info@aesfluids.com

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

