# X-OUT<sup>\*</sup>



## BENEFITS

Combats bicarbonate/carbonate contamination

Performs in high temperature conditions up to 350°F

Effective in pH sensitive polymer based fluid systems



### APPLICATIONS

0.25 - 1.5 gal/bbl for most applications (typical)



#### PHYSICAL PROPERTIES

- Appearance: Colorless to amber colored liquid
- Specific Gravity: 1.02
- Flash Point: 218°F

X-OUT is a liquid amine carbon dioxide scavenger that effectively treats acid gas.



## TREATMENT RECOMMENDATIONS

Typical concentrations of 0.25 to 1.5 gal/bbl for most applications, although higher concentrations may be necessary in extreme conditions.

## PACKAGING AND HANDLING

X-OUT is available in 5 gallon pails or 55 gallon drums. Handle X-OUT as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).





www.aesfluids.com

Phone : 281 556 5628
Email : info@aesfluids..com

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. <sup>†</sup>Marks of AES Drilling Fluids, LLC.

Revision 1.00

