

# EnerSEAL HDD<sup>†</sup> Secures River Crossing Near Fort St. John, British Columbia



## CHALLENGES

Drill a 12 ¼" pilot hole under a river

One offset crossing was abandoned and a second drilled with no returns

Efficiently deliver the crossing minimizing risk of losses



## SOLUTION

EnerSEAL HDD, a robust mixed metal hydroxide system

Leverage unique shear thinning properties to prevent losses and provide superior hole cleaning



## RESULTS

- Clean wellbore eliminated extra cleanout trips
- Crossing drilled 8 days ahead of the 28 day plan
- 71% less waste versus plan

## OVERVIEW

A customer was seeking to drill a trenchless river crossing near Fort St. John in British Columbia. A nearby crossing included a failed initial attempt with the second effort achieved with large volumes of losses.

EnerSEAL HDD was recommended for its highly thixotropic properties which minimize losses while providing superior hole cleaning. The 12 ¼" pilot hole was drilled ahead of plan with a dramatic reduction in waste volumes.

## DETAILS

Prior to drilling, computer modeling was used to simulate hole cleaning efficiency. A detailed fluids program was prepared for proper system blending and maintenance. The EnerSEAL HDD system was mixed on-site to required properties and drilling commenced.

The hole was drilled with no hole cleaning issues, eliminating the need for added trips to remove residual cuttings. An optimized solids control setup was used to leverage the efficiency of the EnerSEAL HDD system, minimizing dilution requirements and waste volumes.

The planned 28 day crossing was delivered 8 days early. Total waste volume was 1480 bbl, 71% less than the expected 4375 bbl.



Optimized solids control equipment in combination with EnerSEAL HDD properties resulted in dramatic waste reduction (above)





## **AES DRILLING FLUIDS**

[www.aesfluids.com](http://www.aesfluids.com)

☎ Phone : 281 556 5628

✉ Email : [info@aesfluids.com](mailto:info@aesfluids.com)

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

