


AES 40

SYNTHETIC INVERT EMULSION



AES DRILLING FLUIDS

DESCRIPTION

ABS 40 is a synthetic-based invert emulsion system using a base oil blend optimized for performance and environmentally sensitive properties, including zero (non-detect) BTEX and polycyclic aromatic hydrocarbons (PAH) when using ABS 40 BASE or ABS 40 BASE LV oils. ABS 40 provides the performance of an invert emulsion system where conventional oil-based systems are prohibited or undesirable.

ABS 40 BASE, the base oil component of the ABS 40 system, is a proprietary blend of linear paraffins, synthetic iso-alkanes, olefins, and aliphatic fluids. Its biodegradability and low toxicity make the ABS 40 system ideal for land applications where operators seek a more environmentally sensitive drilling fluid but require invert emulsion performance.



ABS 40 provides the superior performance sought when utilizing an invert emulsion fluid: inhibition, faster rates of penetration, lubricity, and simplicity while removing many harmful components found in diesel.

Diesel base fluids are characterized by combustion specifications and viscosity may vary significantly. ABS 40 is blended for consistent viscosity, offering improved rheological control for hole cleaning and pressure management. A higher aniline point presents greater compatibility with elastomers, reducing the risk of motor failures.



DESCRIPTION

A B S 4 0

Synthetic invert emulsion
drilling fluid

Base oil features improved
environmental, health, and
safety benefits compared to
diesel



BENEFITS

A B S 4 0

Invert emulsion drilling
performance

Controlled properties enhance
fluid capabilities

Enables drilling in some restricted
areas and enhances overall
environmental impact profile



APPLICATIONS

A B S 4 0

Areas where invert emulsions
are required but diesel is
prohibited

Operations near populated or
sensitive areas where ABS 40
is approved for use

APPLICATION

ABS 40 is ideal anywhere invert emulsion systems are desired and approved for use, but diesel is undesirable or prohibited. In areas where diesel is prohibited, ABS 40 may offer an acceptable alternative, although this must be confirmed with local regulatory agencies. When drilling on private land, ABS 40 offers a more sensitive option with minimal odor and reduced environmental hazards.

ABS 40 is available at densities ranging from 7.5 lbm/gal to 18.4 lbm/gal with conventional weight material. Standard ABS 40 systems exceed 250°F; however, using high temperature additives, ABS 40 is capable of drilling wells exceeding 400°F.

In extended reach well applications, ABS 40 features a controlled, lower viscosity to aid with turbulent flow, which is critical for hole-cleaning. An elevated aniline point aids to extend elastomer life and a higher flash point simplifies transportation requirements.

Optimized solids control equipment aids to limit base fluid consumption due to cuttings retention and reduces base fluid additions for dilution. Supplemental solids control equipment, including drying shakers or cuttings dryers may further extend fluid life, enhance waste reduction, and improve economics.



■ ABS 40 BASE (left) provides a diesel (right) alternative with consistent properties and a superior health, safety, and environmental profile


PERFORMANCE

ABS 40 has been used in over 3,500 wells drilling offshore and on land with excellent performance in unconventional and conventional wells.

Throughout its extensive history, ABS 40 has effectively drilled through a number of formations including shale, carbonates, marl, gumbo and salt.


3500+
WELLS AND COUNTING





AES DRILLING FLUIDS

www.aesfluids.com

© 2023 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.02

