

MULTIFIBER M[†]

PROPRIETARY BLEND OF MEDIUM SIZED FIBROUS MATERIAL

BENEFITS

- Rapid sealing and bridging of permeable of fractured zones.
- Designed to minimize risk of plugging downhole equipment.
- Does not alter fluid properties (inert solid).

APPLICATIONS

- 10 - 30 lb/bbl for sweeps or 3 - 7 lb/bbl for seepage loss control (typical).
- Performs as standalone product or in combination with other materials.
- Higher concentrations may be required for extreme conditions.

PROPERTIES

- Appearance: Granular fibrous blend
- Specific Gravity: 1.4

TREATMENT RECOMMENDATIONS

Treatments typically range from 10 to 30 lb/bbl sweeps. As part of the active system, concentrations range from 3 to 7 lb/bbl. While MULTIFIBER M is designed to minimize risk of plugging downhole tools, verify compatibility with supplier representatives before use.

Particle Size Distribution
(typical, microns)

D ₁₀	41
D ₅₀	613
D ₉₀	1790

PACKAGING AND HANDLING

MULTIFIBER M is available in 25 lb sacks. Handle MULTIFIBER M as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



MULTIFIBER M lost circulation additive.



AES DRILLING FLUIDS



AES DRILLING FLUIDS

www.aesfluids.com

© 2024 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. [†]Marks of AES Drilling Fluids, LLC.

Revision 1.01