

TRU VIS[†]

HIGH-YIELD ORGANOPHILIC CLAY

BENEFITS

- Provides low-shear viscosity to aid in fluid suspension properties.
- Readily yields in oil- or synthetic-based drilling fluids with minimal shear.
- Effective across a broad range of fluid densities and solids concentrations.

APPLICATIONS

- 3 - 5 lb/bbl in the active system (typical).
Treatments are added in 0.5 - 1 lb/bbl increments, observing fluid property changes while circulating.
- Add through the hopper and shear.

PROPERTIES

- Appearance: Tan powder
- Specific Gravity: 1.6

TREATMENT RECOMMENDATIONS

TRU VIS concentrations range from 3 to 5 lb/bbl for most applications. For system treatment, gradually add product in 0.5 to 1 lb/bbl increments and monitor changes in fluid properties as product yields while circulating.

PACKAGING AND HANDLING

TRU VIS is available in 50 lb sacks. Handle TRU VIS as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS



AES DRILLING FLUIDS

www.aesfluids.com

© 2024 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. [†]Marks of AES Drilling Fluids, LLC.

Revision 1.01