

AES MUL X[†]

STANDARD EMULSIFIER PACKAGE FOR THE AES VERT DRILLING FLUID SYSTEM

BENEFITS

- Stabilizes invert emulsion and supplements filtration control.
- Blends with minimal shear.
- Effective across a wide range of oil:water ratios and internal phase salinities.

APPLICATIONS

- AES VERT or similar diesel-based drilling fluid systems. Pilot test as needed.
- 1.0 gal/bbl (typical) for base formulation. Add maintenance treatments as required.

PROPERTIES

- Appearance: Amber liquid
- Specific Gravity: 0.91 - 0.94
- Flash Point: >200°F
- Pour Point: -8°F

TREATMENT RECOMMENDATIONS

AES MUL X is a liquid additive used to prepare and maintain the AES VERT system while drilling. Typical base formulations contain 1 gallon of AES MUL X per barrel of drilling fluid mixed.

AES MUL X works in combination with AES WA II[†] to provide a stable emulsion with oil-wet solids. Maintain product concentration while drilling, monitoring overall drilling fluid properties for treatment requirements.

PACKAGING AND HANDLING

AES MUL X is available in 275 gal totes. Handle AES MUL X as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).





AES DRILLING FLUIDS

www.aesfluids.com

© 2024 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.01