

# DEFOAM A<sup>†</sup>

ALCOHOL-BASED DEFOAMER

## BENEFITS

- Rapidly eliminates foam.
- Effective in brine and water-based systems at low concentrations.

## APPLICATIONS

- 1.3 - 8.0 gallons per 100 bbl (typical) for most applications.
- Can be added directly to active pit.

## PROPERTIES

- Appearance: Light tan liquid
- Specific Gravity: 0.90 - 0.93

## TREATMENT RECOMMENDATIONS

DEFOAM A can be added directly to the active pit. In most applications 1.3 to 8.0 gallons per 100 barrels is effective.

## PACKAGING AND HANDLING

DEFOAM A is available in 5 gallon pails and 55 gallon drums. Handle DEFOAM A as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



In a lab test, a sample demonstrated high foaming tendencies (left). A treatment of 0.1 lb/bbl DEFOAM A dramatically reduced foaming (right). Note: base fluid color added for contrast.





**AES DRILLING FLUIDS**

[www.aesfluids.com](http://www.aesfluids.com)

© 2024 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.01