

ENERMOD[†]

LIQUID POLYMERIC VISCOSIFIER

BENEFITS

- Provides a shear thinning rheological profile with increased low shear rate viscosity.
- Increases carrying capacity and minimizes barite settling risk.
- Effective in temperatures up to 350°F

APPLICATIONS

- Typically added at 0.1 - 5.0 lb/bbl for most applications.
- Add in 0.1 - 0.25 lb/bbl increments to active system; allow two circulations for complete dispersion.

PROPERTIES

- Appearance: Amber liquid
- Specific Gravity: 1.02
- Flash Point: 160°F

TREATMENT RECOMMENDATIONS

Typical concentrations of 0.1 to 5.0 lb/bbl for most applications. Treat the circulating system in 0.1 lb/bbl increments, allowing to full circulations for complete yield.

Pilot testing recommended to determine the appropriate concentration for a specific scenario.

PACKAGING AND HANDLING

ENERMOD is available in 5 gallon pails. Handle ENERMOD as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).





AES DRILLING FLUIDS

www.aesfluids.com

© 2024 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.01