

ENERPAC LV⁺

HIGH PURITY POLYANIONIC CELLULOSE

BENEFITS

- Enhances filter cake quality, lowering overall fluid loss with minimal viscosity contribution.
- Disperses rapidly.
- Non-fermenting - no preservative required.

APPLICATIONS

- 0.25 - 3.0 lb/bbl (typical) for most water based applications.
- Add through the hopper at no faster than 20 - 30 minutes per sack.

PROPERTIES

- Appearance: Off-white powder
- Specific Gravity: 1.5
- Solubility: Water and saturated brines

TREATMENT RECOMMENDATIONS

Typical concentrations range between 0.25 to 3 lb/bbl for most applications. ENERPAC LV should be mixed through a hopper at a controlled rate no faster than 20 - 30 minutes per sack.

Pilot testing recommended to determine the appropriate concentration for a specific scenario.

PACKAGING AND HANDLING

ENERPAC LV is available in 50 lb sacks. Handle ENERPAC LV as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



ENERPAC LV
polyanionic
cellulose
(PAC)





AES DRILLING FLUIDS

www.aesfluids.com

© 2024 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.01