

# SHALETEx II<sup>†</sup>

SULFONATED ASPHALT BLEND

## BENEFITS

- Effectively inhibits hydration and sloughing of shales.
- Enhances filter cake quality, lowering overall fluid loss.

## APPLICATIONS

- 3 - 5 lb/bbl to active system (typical)
- Supplemental treatment recommended prior to logging and casing runs.

## PROPERTIES

- Appearance: Black powder
- Specific Gravity: 1.1 - 1.6

## TREATMENT RECOMMENDATIONS

SHALETEx II is added at concentrations between 3 to 5 lb/bbl for most applications, although higher concentrations may be necessary under extreme conditions. Supplemental treatment is recommended prior to logging and casing runs.

Pilot testing recommended to determine the appropriate concentration for a specific scenario.

## PACKAGING AND HANDLING

SHALETEx II is available in 50 lb sacks. Handle SHALETEx II as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).





**AES DRILLING FLUIDS**

[www.aesfluids.com](http://www.aesfluids.com)

© 2024 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.01