

# WALLPLEX<sup>+</sup>

## WALL CAKE ADDITIVE

### BENEFITS

- Enhances filter cake quality, lowering overall fluid loss improves lubricity.
- Compatible with freshwater and many brine fluids.

### APPLICATIONS

- 4 - 8 lb/bbl to active system or 5 - 10 lb/bbl added to sweeps.
- Supplemental treatment recommended prior to logging and casing runs.

### PROPERTIES

- Appearance: Dark grey powder
- Specific Gravity: 1.4 - 1.8

### TREATMENT RECOMMENDATIONS

WALLPLEX is added to the active system at concentrations between 4 to 8 lb/bbl or added to sweeps at 5 to 10 lb/bbl for most applications. Higher concentrations may be necessary under extreme conditions. Supplemental treatment is recommended prior to logging and casing runs.

Pilot testing is recommended to determine the appropriate concentration for a specific scenario.

### PACKAGING AND HANDLING

WALLPLEX is available in 50 lb sacks. Handle WALLPLEX as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



Filter cake formed after treating with 6 lb/bbl WALLPLEX





**AES DRILLING FLUIDS**

[www.aesfluids.com](http://www.aesfluids.com)

© 2024 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.01